



CAT. NO. SS	CAT. NO. TT	CANCELLOUS SCREWS Ø 4.0 MM (F.TH)
212.012	605.012	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 12 MM
212.014	605.014	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 14 MM
212.016	605.016	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 16 MM
212.018	605.018	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 18 MM
212.020	605.020	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 20 MM
212.022	605.022	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 22 MM
212.024	605.024	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 24 MM
212.025	605.025	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 25 MM
212.026	605.026	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 26 MM
212.028	605.028	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 28 MM
212.030	605.030	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 30 MM
212.032	605.032	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 32 MM
212.034	605.034	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 34 MM
212.035	605.035	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 35 MM
212.036	605.036	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 36 MM
212.038	605.038	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 38 MM
212.040	605.040	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 40 MM
212.042	605.042	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 42 MM
212.045	605.045	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 45 MM
212.050	605.050	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 50 MM
212.055	605.055	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 55 MM
212.058	605.058	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 58 MM
212.060	605.060	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 60 MM
212.065	605.065	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 65 MM
212.070	605.070	CANCELLOUS SCREWS Ø 4.0 MM (F.TH) X 70 MM

Specification

- Available in 10mm to 60mm length with 4.0mm diameter.
- Fully threaded shaft.
- Available in both Stainless Steel & Titanium.

Indication for use

- It is used in the fixation of Small Fragment Plates