



CAT. NO.	METAL	CANNULATED SCREWS Ø3.5MM (P.TH)
217.120	SS	Cannulated Screws Ø 3.5mm (P.th) x 20mm
217.124	SS	Cannulated Screws Ø 3.5mm (P.th) x 24mm
217.125	SS	Cannulated Screws Ø 3.5mm (P.th) x 25mm
217.128	SS	Cannulated Screws Ø 3.5mm (P.th) x 28mm
217.130	SS	Cannulated Screws Ø 3.5mm (P.th) x 30mm
217.132	SS	Cannulated Screws Ø 3.5mm (P.th) x 32mm
217.135	SS	Cannulated Screws Ø 3.5mm (P.th) x 35mm
217.140	SS	Cannulated Screws Ø 3.5mm (P.th) x 40mm
217.145	SS	Cannulated Screws Ø 3.5mm (P.th) x45mm
217.150	SS	Cannulated Screws Ø 3.5mm (P.th) x 50mm
217.155	SS	Cannulated Screws Ø 3.5mm (P.th) x 55mm
217.160	SS	Cannulated Screws Ø 3.5mm (P.th) x 60mm
217.165	SS	Cannulated Screws Ø 3.5mm (P.th) x 65mm
217.170	SS	Cannulated Screws Ø 3.5mm(P.th) x 70mm
217.175	SS	Cannulated Screws Ø 3.5mm (P.th) x 75mm
217.180	SS	Cannulated Screws Ø 3.5mm (P.th) x 80mm

Specification

- Available in 20-80mm length with 3.5mm diameter.
- Partially threaded shaft.
- Available in stainless steel.

Indication for use

- Cannulated screws are used as lag screws for fixation of diaphyseal fractures.
- It is used in the fixation of Small Fragment Plates.