



CAT. NO. SS	METAL	CANNULATED SCREWS Ø 4.5MM (P.TH)
220.616	SS	Cannulated Screws Ø 4.5mm (P.th) x 30mm
220.619	SS	Cannulated Screws Ø 4.5mm (P.th) x 35mm
220.622	SS	Cannulated Screws Ø 4.5mm (P.th) x 40mm
220.625	SS	Cannulated Screws Ø 4.5mm (P.th) x 45mm
220.627	SS	Cannulated Screws Ø 4.5mm (P.th) x 48mm
220.628	SS	Cannulated Screws Ø 4.5mm (P.th) x 50mm
220.631	SS	Cannulated Screws Ø 4.5mm (P.th) x 55mm
220.634	SS	Cannulated Screws Ø 4.5mm (P.th) x 60mm
220.637	SS	Cannulated Screws Ø 4.5mm (P.th) x 65mm
220.640	SS	Cannulated Screws Ø 4.5mm (P.th) x 70mm
220.643	SS	Cannulated Screws Ø 4.5mm (P.th) x 75mm
220.646	SS	Cannulated Screws Ø 4.5mm (P.th) x 80mm

## Specification

- Available in 30-80mm length with 4.5mm diameter.
- Partially threaded shaft.
- Available in stainless steel.

## Indication for use

- Cannulated screws are used as lag screws for fixation of diaphyseal fractures.
- It is used in the fixation of Small Fragment Plates.