



CAT. NO. SS	CAT. NO. TT	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM
336.012	636.012	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 12MM
336.014	636.014	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 14MM
336.016	636.016	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 16MM
336.018	636.018	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 18MM
336.020	636.020	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 20MM
336.022	636.022	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 22MM
336.024	636.024	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 24MM
336.025	636.025	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 25MM
336.026	636.026	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 26MM
336.028	636.028	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 28MM
336.030	636.030	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 30MM
336.032	636.032	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 32MM
336.034	636.034	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 34MM
336.035	636.035	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 35MM
336.036	636.036	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 36MM
336.038	636.038	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 38MM
336.040	636.040	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 40MM
336.045	636.045	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 45MM
336.050	636.050	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 50MM
336.055	636.055	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 55MM
336.060	636.060	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 60MM
336.062	636.062	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 62MM
336.064	636.064	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 64MM
336.065	636.065	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 65MM
336.066	636.066	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 66MM
336.068	636.068	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 68MM
336.070	636.070	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 70MM
336.075	636.075	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 75MM
336.080	636.080	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 80MM
336.085	636.085	LC-LCP CANCELLOUS (F.TH) SCREW Ø 4.0MM X 85MM

Specification

- Available in 12mm to 85mm length with 4.0mm diameter.
- Fully threaded shaft.
- Available in both Stainless Steel & Titanium.

Indication for use

- It is used in the fixation of Small Fragment Plates.