



CAT. NO.	METAL	Tapered Half pin Dia 4 mm
358,580	SS	Tapered Half Pin 4.0mm x 18th x 50 mm
358,620	SS	Tapered Half Pin 4.0mm x 20th x 60 mm
358,625	SS	Tapered Half Pin 4.0mm x 25th x 60 mm
358,720	SS	Tapered Half Pin 4.0mm x 20th x 70 mm
358,725	SS	Tapered Half Pin 4.0mm x 25th x 70 mm
358,820	SS	Tapered Half Pin 4.0mm x 20th x 80 mm
358,825	SS	Tapered Half Pin 4.0mm x 25th x 80 mm
358,830	SS	Tapered Half Pin 4.0mm x 30th x 80 mm
358,920	SS	Tapered Half Pin 4.0mm x 20th x 100 mm
358,925	SS	Tapered Half Pin 4.0mm x 25th x 100 mm
358,930	SS	Tapered Half Pin 4.0mm x 30th x 170 mm

Specification

- Tapered Half pin available in Stainless steel.
- It is available in 50-170mm length with 4mm Dia.

Indication for use

- Tapered half pin use in vitro mechanical study was performed to compare the stiffness, maximum load, and cyclic load-to-failure of a new external fixation half-pin design utilizing a tapered thread-run-out (TRO) feature with currently available positive profile thread (PP) half-pins.

