


 Ø5.5 MM

CAT. NO.	METAL	SPINAL ROD 5.5MM
665.440	TT	Spinal Rod- Ø 5.5 mm x 40 mm
665.445	TT	Spinal Rod- Ø 5.5 mm x 45 mm
665.450	TT	Spinal Rod- Ø 5.5 mm x 50 mm
665.460	TT	Spinal Rod- Ø 5.5 mm x 60 mm
665.465	TT	Spinal Rod- Ø 5.5 mm x 65 mm
665.470	TT	Spinal Rod- Ø 5.5 mm x 70 mm
665.480	TT	Spinal Rod- Ø 5.5 mm x 80 mm
665.490	TT	Spinal Rod- Ø 5.5 mm x 90 mm
665.500	TT	Spinal Rod- Ø 5.5 mm x 100 mm
665.510	TT	Spinal Rod- Ø 5.5 mm x 110 mm
665.520	TT	Spinal Rod- Ø 5.5 mm x 120 mm
665.530	TT	Spinal Rod- Ø 5.5 mm x 130 mm
665.540	TT	Spinal Rod- Ø 5.5 mm x 140 mm
665.550	TT	Spinal Rod- Ø 5.5 mm x 150 mm
665.560	TT	Spinal Rod- Ø 5.5 mm x 160 mm
665.570	TT	Spinal Rod- Ø 5.5 mm x 170 mm
665.580	TT	Spinal Rod- Ø 5.5 mm x 180 mm
665.590	TT	Spinal Rod- Ø 5.5 mm x 190 mm
665.600	TT	Spinal Rod- Ø 5.5 mm x 200 mm
665.650	TT	Spinal Rod- Ø 5.5 mm x 250 mm
665.700	TT	Spinal Rod- Ø 5.5 mm x 300 mm
665.725	TT	Spinal Rod- Ø 5.5 mm x 350 mm
665.750	TT	Spinal Rod- Ø 5.5 mm x 400 mm
665.775	TT	Spinal Rod- Ø 5.5 mm x 450 mm
665.800	TT	Spinal Rod- Ø 5.5 mm x 500 mm

Specification

- Spinal Rod available in Titanium.
- Available length 80 & 100mm with 5.5mm diameter.

Indication for use

- It is a component of Spine Fixation System intended for use in the pedicle Screw fixation or in the anterolateral lateral spine fixation system.
- In the event that additional torsion stability is required, a cross connector assembled with 5.5mm connecting rod is used.
- The device is indicated for the treatment of degenerative disc disease, Spondylolisthesis, trauma (fracture or dislocation), deformity, or curvature (scoliosis, kyphosis, and lordosis) tumor, stenosis, pseudoarthrosis, and previous failed fusion.

