

MONOAXIAL REDUCTION SCREW (5.5MM ROD SYSTEM)



| CAT. NO. | METAL | MONOAXIAL REDUCTION SCREW (5.5MM ROD SYSTEM) |
|----------|-------|---|
| 646.412 | TT | MONOAXIAL REDUCTION SCREW 5.5MM ROD SYSTEM 5.5MM X 35MM |
| 646.413 | TT | MONOAXIAL REDUCTION SCREW 5.5MM ROD SYSTEM 5.5MM X 40MM |
| 646.414 | TT | MONOAXIAL REDUCTION SCREW 5.5MM ROD SYSTEM 5.5MM X 45MM |
| 646.415 | TT | MONOAXIAL REDUCTION SCREW 5.5MM ROD SYSTEM 5.5MM X 50MM |
| 646.422 | TT | MONOAXIAL REDUCTION SCREW 5.5MM ROD SYSTEM 6.5MM X 35MM |
| 646.423 | TT | MONOAXIAL REDUCTION SCREW 5.5MM ROD SYSTEM 6.5MM X 40MM |
| 646.424 | TT | MONOAXIAL REDUCTION SCREW 5.5MM ROD SYSTEM 6.5MM X 45MM |
| 646.425 | TT | MONOAXIAL REDUCTION SCREW 5.5MM ROD SYSTEM 6.5MM X 50MM |

Specification

- Monoaxial screws available in Titanium.
- Available length 35,40,45 & 50mm with 5.5 & 6.5mm diameter.

Indication for use

- Monoaxial Reduction screw is used for stabilization of the occipitocervical junction.