

Ø6.5MM CANCELLOUS SCREW FOR T.H.R



CAT. NO.	METAL	Ø6.5MM CANCELLOUS SCREW FOR T.H.R
752.008S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 8.0MM
752.015S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 15.0MM
752.020S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 20.0MM
752.025S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 25.0MM
752.030S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 30.0MM
752.035S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 35.0MM
752.040S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 40.0MM
752.045S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 45.0MM
752.050S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 50.0MM
752.055S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 55.0MM
752.060S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 60.0MM
752.065S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 65.0MM
752.070S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 70.0MM
752.075S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 75.0MM
752.080S	TT	Ø6.5MM CANCELLOUS SCREW FOR T.H.R 80.0MM

Specification

- Ø6.5MM Cancellous screw for T.H.R is available in Titanium.

Indication for use

- 6.5 mm Cancellous Screw is intended for fracture fixation of large bones and large bone fragments.