



| HERBUT SCREW INSTRUMENT SET |   |     |
|-----------------------------|---|-----|
| SR. NO.                     | NAME OF INSTRUMENT                                      | QTY |
| 1                           | DRILL SLEEVE $\Phi 2.5$                                 | 1   |
| 2                           | WIRE SLEEVE $\Phi 2.5/\Phi 1.2$                         | 1   |
| 3                           | CANNULATED DRILL BIT WITH LIMITATOR $\Phi 2.5/\Phi 1.2$ | 1   |
| 4                           | GUIDE WIRE $\Phi 1.2*150$                               | 1   |
| 5                           | GUIDE WIRE $\Phi 1.2*150$                               | 1   |
| 6                           | CANNULATED COUNTERSINK $\Phi 4.3/\Phi 1.2$              | 1   |
| 7                           | CANNULATED SCREWDRIVER SW2.5/ $\Phi 1.2$                | 1   |
| 8                           | SCREWDRIVER SW2.5                                       | 1   |
| 9                           | DRILL SLEEVE $\Phi 2.8$                                 | 1   |
| 10                          | WIRE SLEEVE $\Phi 2.8/\Phi 1.2$                         | 1   |
| 11                          | CANNULATED DRILL BIT WITH LIMITATOR $\Phi 2.8/\Phi 1.2$ | 1   |
| 12                          | GUIDE WIRE $\Phi 1.2*150$                               | 1   |
| 13                          | GUIDE WIRE $\Phi 1.2*150$                               | 1   |
| 14                          | CANNULATED COUNTERSINK $\Phi 5.0$                       | 1   |
| 15                          | DRILL SLEEVE $\Phi 2.0$                                 | 1   |
| 16                          | WIRE SLEEVE $\Phi 2.0/\Phi 0.8$                         | 1   |
| 17                          | CANNULATED SCREWDRIVER SW1.5/ $\Phi 0.8$                | 1   |
| 18                          | SCREWDRIVER SW1.5                                       | 1   |
| 19                          | CANNULATED DRILL BIT WITH LIMITATOR $\Phi 2.0/\Phi 0.8$ | 1   |
| 20                          | GUIDE WIRE $\Phi 0.8*150$                               | 1   |
| 21                          | GUIDE WIRE $\Phi 0.8*150$                               | 1   |
| 22                          | CANNULATED COUNTERSINK $\Phi 3.0/\Phi 0.8$              | 1   |
| 23                          | DRILL SLEEVE $\Phi 2.2$                                 | 1   |
| 24                          | WIRE SLEEVE $\Phi 2.2/\Phi 1.0$                         | 1   |
| 25                          | CANNULATED SCREWDRIVER SW2.0/ $\Phi 1.0$                | 1   |
| 26                          | SCREWDRIVER SW2.0                                       | 1   |
| 27                          | CANNULATED DRILL BIT WITH LIMITATOR $\Phi 2.2/\Phi 1.0$ | 1   |
| 28                          | GUIDE WIRE $\Phi 1.0*150$                               | 1   |
| 29                          | GUIDE WIRE $\Phi 1.0*150$                               | 1   |
| 30                          | CANNULATED COUNTERSINK $\Phi 3.5/\Phi 1.0$              | 1   |
| 31                          | CLEAN STYLET $\Phi 1.0*150$                             | 1   |
| 32                          | STRAIGHT HANDLE   | 1   |
| 33                          | STRAIGHT HANDLE   | 1   |
| 34                          | SCREW HOLDING FORCEP                                    | 1   |
| 35                          | HEX KEY SW2.5   | 1   |
| 36                          | DEPTH GAUGE   | 1   |
| 37                          | ALUMINIUM BOX   | 1   |

## Specification

- All instruments are available in SS.

## Indication for use

- The Herbert screw instrument set is indicated for internal fixation of small bone fractures, particularly scaphoid fractures, nonunions, and osteotomies. It provides stable, headless compression fixation ideal for areas requiring minimal soft tissue disruption.

