



| PFN IMPLANT SYSTEM (DOUBLE SCREW SYSTEM) |
|--|
| LONG PROXIMAL FEMORAL NAILS 130* (LONG P.F.N.) |
| LONG PROXIMAL FEMORAL NAILS ø 9 MM |
| LONG PROXIMAL FEMORAL NAILS ø 10 MM |
| LONG PROXIMAL FEMORAL NAILS ø 11 MM |
| TROCHANTERIC FEMORAL NAILS 130* (TFN) |
| TROCHANTERIC NAILS ø 09 MM |
| TROCHANTERIC NAILS ø 10 MM |
| TROCHANTERIC NAILS ø 11 MM |
| TROCHANTERIC NAILS ø 12 MM |
| SHORT PROXIMAL FEMORAL NAILS 130* (SHORT P.F.N.) |
| PROXIMAL FEMORAL NAILS ø 09 MM |
| PROXIMAL FEMORAL NAILS ø 10 MM |
| PROXIMAL FEMORAL NAILS ø 11 MM |
| PROXIMAL FEMORAL NAILS ø 12 MM |
| END CAP FOR NAIL EXTENSION FOR PFN |
| HIP PIN ø 6.2 MM |
| FEMORAL NECK SCREW ø 8.0 MM |
| LOCKING BOLT (SELF TAPPING) ø 4.9 MM |

| PFN (DOUBLE SCREW)INSTRUMENT SET | | |
|----------------------------------|---|-----|
| CAT. NO. | NAME OF INSTRUMENT | QTY |
| 909.100 | PFN/TFN JIG | 1 |
| 909.105 | PROTECTION SLEEVE Ø 12 X 10 MM | 1 |
| 909.110 | PROTECTION SLEEVE Ø 10 X 08 MM | 2 |
| 909.115 | WIRE SLEEVE Ø 8 X 2.5 MM | 1 |
| 909.120 | TROCAR Ø 8.0 MM | 1 |
| 909.125 | NAIL CONNECTING BOLT FOR PFN | 1 |
| 909.135 | HEXAGONAL POLYAXIAL WRENCH Ø 8 MM | 1 |
| 909.140 | DRILL SLEEVE Ø 8 X 4.0MM | 1 |
| 909.145 | PROTECTION SLEEVE FOR TROCHANTERIC REAMERSOLAPUR TYPE | 1 |
| 909.150 | CANNULATED/TROCHANTERIC REAMER WITH THANDLE Ø 15.0 MM | 1 |
| 909.155 | HIP PIN REAMER CANNULATED Ø 6.2 MM | 1 |
| 909.160 | FEMORAL NECK SCREW REAMER CANNULATED Ø 8 MM | 1 |
| 909.162 | HIP PIN CANNULATED TAP 6.2MM | 1 |
| 909.164 | FEMORAL NECK CANNULATED TAP 8.0MM | 1 |
| 903.105 | INSERTION DRIVING HEAD | 1 |
| 903.110 | RAM | 1 |
| 903.115 | RAM ROD | 1 |
| 903.120 | WRENCH | 1 |
| 903.160 | GUIDE ROD Ø 2.5 MM X 95CM | 1 |
| 903.165 | REAMING ROD WITH OLIVE POINT Ø 2.5 MM X 95CM | 1 |
| 903.155 | GUIDE WIRE HOLDER | 1 |
| 401.100 | GUIDE WIRE FOR PFN | 3 |
| 426.240 | KUNTSCHER'S DIAMOND POINTED AWL CURVED | 1 |
| 439.500 | DRILL BIT Ø 4.0MM X 300 MM NON-COUPLING | 1 |
| 439.655 | I.L. SCREW DRIVER 4.5MM | 1 |
| 467.375 | SCREW DRIVER CANNULATED Ø 5.5 MM | 1 |
| 467.375 | GUIDE WIRE FORPFN Ø 2.5MM | 2 |
| 909.170 | TROCAR Ø 10 MM | 1 |
| 903.105 | DRIVING HEAD | 1 |
| 903.145 | TISSUE PROTECTOR | 1 |
| 909.101 | INSTRUMENT BOX | 1 |

Specification

- Implants are available in TT & SS.
- Instruments are available in SS.

Indication for use

- The PFN SYSTEM (DOUBLE SCREW SYSTEM) is intended for the internal fixation of fractures in the proximal femur. It is specifically indicated for intertrochanteric fractures, subtrochanteric fractures, and certain types of femoral neck fractures. The system provides intramedullary stabilization, allowing for controlled fracture compression, rotational stability, and early weight-bearing.

